

Special Systems | VK-200 Clean Agent System



Safe, proven, dependable - VK-200 fire extinguishing system with clean agent FM-200® (HFC-227ea)

cULus Listed, FM Approved
Class A, B, C Fire Classification
Minimum Design Concentration 6.7% (Class A)
360 psi
Three Tank Sizes: 130, 270, and 370 lbs
Four Nozzle Sizes: 1/2", 1", 1-1/2", and 2"
Two Valve Sizes: 1-1/2" and 2"
Electric Release (Optional Manual Release)
NOEL: 9% by volume
LOEL: 10.5% by volume
Zero ozone depletion potential
EPA SNAP approved

- Highly-specialized protection for sensitive areas - extinguishes without harming high-value assets - leaving no residue, no cleanup, minimal downtime
- Applications include data processing and telecommunication facilities, computer and server rooms, control rooms, medical/laboratory facilities, historical sites, etc.
- FM-200® also has widespread use in aviation and marine applications as well as cultural properties, libraries, and museums
- FM-200® (HFC-227ea) is widely used throughout the world with years of positive performance history. FM-200® is in use in over 100,000 applications, in more than 70 countries.
- Excellent price-to-performance ratio
- Causes no damage through short circuits or residue left on sensitive components
- Rapid extinguishing effect - total flooding of room achieved in under 10 seconds
- Non-toxic, safe for human occupancy
- System design support available from Viking -- Contact your Viking SupplyNet Sales Manager for a quote request
- For additional product information, please visit us online at vikinggroupinc.com or contact Viking's Technical Services team at techsvcs@vikingcorp.com

*Viking Corporation
210 N Industrial Park Drive
Hastings, MI 49058
Phone: (269) 945-9501
Fax: (269) 945-9599
www.vikinggroupinc.com*